NSN 5905-01-146-2876

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-146-2876

250 to 25	Tompurature Coefficient Of Pecistance In Pom Per Deg Colcius:
Electrical Resistance: 14.300 ohms Resistance Tolerance In Percent: 1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diamete: 0.109 inches Body Diamete: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal ech end Test Data Document: 14349-mill-155182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain of the control of the publications, reflecting general type data on certain of the publications, reflecting general type data on certain of the publications, reflecting general type data on certain of the procent in packaged untered publications, reflecting general type data on certain of the procent in packaged untered publications, reflecting general type data on certain of the publications, reflecting general type data on certain of the procent in the publications, reflecting general type data on certain of the procent in the procent in the publications, reflecting general type data on certain of the publications, reflecting general type data on certain of the procent in the procent in the procent in the publications, reflecting general type data on certain in the procent in the procen	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
14.300 ohms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 175.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Terminal Length: 1.500 inches Body Diamete: 0.109 inches Body Diamete: 0.109 inches Body Diamete: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating in Watts: 0.100 fore air Unpackaged Unit Welght: 0.300 grams Style Designator: Axial terminal ech end Test Data Document: 81349-mill-r.55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Diameter: 0.100 inches inches Power Dissipation Rating in Watts: 0.100 inches inche	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Diameter: 0.250 inches Power Dissipation Rating In Watts: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 0.3149-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Joineter: 0.109 inches Power Dissipation Rating In Watts: 0.250 inches Power Dissipation Rating In Watts: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 0.4149-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Pailure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Diameter: 0.250 inches Body Length: 0.250 inches Power Dissipation Rating in Watts: 0.100 free air Unpackaged Unit Weight: 3.0300 grams Style Designator: Axial terminal each end Test Data Document: 01439-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 0.141 Syle Posification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain of transit can be designed and certain of the process of the process of the prochase of th	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Diameter: 0.109 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Body Length: 0.250 inches Body Length: 0.250 inches Soloy Diameter: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 01349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.1001 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 01349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
-55.0 to 175.0 inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, reflecting general type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	·
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forertain of the property of the	
Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Terminal Length: 1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
1.500 inches Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
0.250 inches Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Power Dissipation Rating In Watts: 0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
0.100 free air Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Unpackaged Unit Weight: 0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
0.300 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	•
Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
On additional to the Delta	
Specification Data:	
81349-mil-r-55182/1 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	Unit Ut Weasure:
Demilitarization:	

No

NSN 5905-01-146-2876

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0