

View Online at <https://aerobasegroup.com/nsn/5905-01-147-0765>

Section Quantity:

2

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.120 inches

Body Length:

0.190 inches

Body Width:

0.480 inches

Body Height:

0.250 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

230.0

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

2.00 inch-ounces

Maximum Stop Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.300 inches

Terminal Location:

Dual inline

Mounting Method:

Terminal

Features Provided:

Humidity proof

Cubic Measure:

0.023 cubic inches

Electrical Resistance Per Section:

100.000 percent, rated amperes c and better

Rotary Actuator Travel In Angular Deg:

230.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary at 10'30 oclock

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 all sections

Standard Taper Curve Per Section:

A all sections

Special Features:

Eight pin dip

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0