

View Online at <https://aerobasegroup.com/nsn/5905-01-147-0765>

**Section Quantity:**

2

**Body Style:**

Rectangular

**Reliability Indicator:**

Not established

**Terminal Length:**

0.120 inches

**Body Length:**

0.190 inches

**Body Width:**

0.480 inches

**Body Height:**

0.250 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

230.0

**Maximum Starting Torque:**

2.00 inch-ounces

**Maximum Running Torque:**

2.00 inch-ounces

**Maximum Stop Torque:**

5.00 inch-ounces

**Center To Center Distance Between Terminals:**

0.300 inches

**Terminal Location:**

Dual inline

**Mounting Method:**

Terminal

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.023 cubic inches

**Electrical Resistance Per Section:**

100.000 percent, rated amperes c and better

**Rotary Actuator Travel In Angular Deg:**

230.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.100 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 all sections

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-100.0/+100.0 all sections

**Power Dissipation Rating Per Section In Watts:**

0.5 7th secondary at 10'30 oclock

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 all sections

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Special Features:**

Eight pin dip

**Terminal Type And Quantity:**

8 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0