NSN 5905-01-147-3624

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-147-3624 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.061 inches **Shaft Diameter:** 0.241 inches **Shaft Length:** 0.532 inches **Mounting Bushing Length:** 0.340 inches **Body Length:** 0.800 inches **Actuator Type:** Recessed drive with slot **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over more than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.0 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 0.1 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Special Features:** Drilled hole through shaft dia

6 turret

Terminal Type And Quantity:

NSN 5905-01-147-3624

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Sneit Lite:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A002a0