NSN 5905-01-147-5875

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-147-5875

Towns are true Oct Mission to Of Paristones In Page Page October						
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:						
-50.0/+50.0						
Electrical Resistance:						
1.270 ohms						
Resistance Tolerance In Percent:						
-1.000/+1.000						
Ambient Tempurature In Deg Celsius At Full Rated Power:						
25.0						
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:						
275.0						
Tempurature Range Of Tempurature Coefficient In Deg Celsius:						
-55.0/+275.0						
Inclosure Method:						
Encased						
Terminal Type:						
Tab, solder lug						
Reactance Characteristic:						
Noninductive						
Reliability Indicator:						
Established						
Reliability Failure Rate Level In Percent:						
0.010						
Terminal Length:						
0.438 inches						
Body Length:						
1.938 inches						
Body Width:						
0.594 inches						
Body Height:						
0.625 inches						
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:						
1.562 inches						
Power Dissipation Rating In Watts:						
10.000 free air						
Terminal Width:						
0.140 inches						
Mounting Hole Size:						
0.125 inches						
Cubic Measure (non-core):						
0.719 cubic inches						

35.000 grams

NSN 5905-01-147-5875

Wire Wound Fixed Resistor - Page 2 of 2



~ ·					
Styl	ם ו	126	เตท	ato	ŀ۲۰
Oty:		-	ıyı,	ato	

Axial terminal (s)

Test Data Document:

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-39009/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0