NSN 5905-01-147-7759

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-147-7759 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 0.430 inches **Terminal Length:** 0.180 inches **Body Diameter:** 0.385 centimeters **Body Length:** 0.200 inches **Overall Diameter:** 0.385 inches **Shaft Bearing Type:** Bearing **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 190.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 12.00 inch-ounces **Center To Center Distance Between Terminals:** 0.344 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Rear end **Mounting Method: Terminal Cubic Measure:** 0.050 cubic inches **Electrical Resistance Per Section:** 100.000 ohms c and better flooring **Rotary Actuator Travel In Angular Deg:**

Center To Center Distance Between Center Terminal And Outside Terminal:

0.172 inches

NSN 5905-01-147-7759

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 7th secondary quality
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:

No

Fiig:

A002a0

Demilitarization: