

View Online at <https://aerobasegroup.com/nsn/5905-01-148-3241>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.3750 inches

Pilot Length:

0.0620 inches

Overall Length:

1.563 inches

Undercut Diameter:

0.400 inches

Undercut Width:

0.0630 inches

Body Diameter:

0.500 inches

Shaft Diameter:

0.0935 inches

Shaft Length:

0.375 inches

Body Length:

1.188 inches

Overall Diameter:

0.844 inches

Mounting Lip Diameter:

0.5000 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3610.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Maximum Stop Torque:

20.00 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.003 inches

Lateral Runout:

0.003 inches

Pilot Diameter Runout:

0.00200 inches

Shaft Radial Play:

0.002 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Cubic Measure:

0.178 cubic inches

Electrical Resistance Per Section:

2.000 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

3620.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-400.0/+400.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 7th secondary quality

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

7 oclock all primaries

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0