NSN 5905-01-148-4060

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-148-4060 **Section Quantity:** 2 **Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.250 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.025 inches **Body Length:** 0.875 inches **Body Width:** 0.531 inches **Body Height:** 0.531 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 265.0 **Maximum Starting Torque:** 5.50 inch-ounces **Maximum Running Torque:** 5.50 inch-ounces **Maximum Stop Torque:** 16.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Lower adjacent side single row **Mounting Method: Terminal Features Provided:** Humidity proof

Cubic Measure:

0.219 cubic inches

NSN 5905-01-148-4060

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
200.000 kilohms all sections
Rotary Actuator Travel In Angular Deg:
295.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
100.0 to 100.0 all sections
Power Dissipation Rating Per Section In Watts:
0.25 free air 1st section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Terminal Type And Quantity:
6 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4002a0