NSN 5905-01-148-4474

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-148-4474 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.357 inches **Body Length:** 1.445 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.90 inch-ounces **Maximum Running Torque:** 0.70 inch-ounces **Maximum Stop Torque:** 75.00 inch-ounces **Shaft End Play:** 0.010 inches **Lateral Runout:** 0.005 inches **Pilot Diameter Runout:** 0.003 inches **Shaft Radial Play:** 0.003 inches

Screw Thread Diameter: 0.375 inches **Screw Thread Series Designator:**

Unef

NSN 5905-01-148-4474

Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Cubic Measure:
0.868 cubic inches
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary at 10'30 oclock
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Function Characteristic Per Section: 6 oclock all primaries
6 oclock all primaries
6 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
6 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections
6 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
6 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections
6 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Precious Material And Location:
6 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Precious Material And Location: Terminal surfaces gold
6 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Precious Material And Location: Terminal surfaces gold Precious Material:
6 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Precious Material And Location: Terminal surfaces gold Precious Material: Gold
6 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity:
6 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity: 6 tab, solder lug
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity: 6 tab, solder lug Shelf Life:
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure:
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Precious Material And Location: Terminal surfaces gold Precious Material: Gold Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: