Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-148-9185

Section Quantity:

1

Body Style:

Rectangular w/bushing

**Reliability Indicator:** 

Not established

Shaft Diameter:

0.115 inches

Shaft Length:

0.250 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.750 inches

Body Width:

## 0.314 inches

**Body Height:** 

0.315 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

9720.0

Maximum Starting Torque:

8.00 inch-ounces

Maximum Running Torque:

8.00 inch-ounces

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

28.0

**Terminal Location:** 

Rear end

**Mounting Method:** 

Standard bushing

**Features Provided:** 

Humidity proof

**Electrical Resistance Per Section:** 

200.000 ohms single section

## NSN 5905-01-148-9185

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

9720.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

**Actuator Travel Control Feature:** 

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

---

Fiig:

A002a0