NSN 5905-01-148-9187 Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



Nonprecision Nonwire Wound Variable Resistor
View Online at https://aerobasegroup.com/nsn/5905-01-148-9187
Section Quantity:
1
Body Style:
Rectangular w/bushing
Reliability Indicator:
Not established
Shaft Diameter:
0.115 inches
Shaft Length:
0.250 inches
Mounting Bushing Length:
0.250 inches
Body Length:
1.750 inches
Body Width:
0.314 inches
Body Height:
0.315 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9720.0
Maximum Starting Torque:
8.00 inch-ounces
Maximum Running Torque:
8.00 inch-ounces
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
28.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Humidity proof

**Electrical Resistance Per Section:** 

20.000 kilohms single section

## NSN 5905-01-148-9187

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9720.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Powers
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: