

View Online at https://aerobasegroup.com/nsn/5905-01-149-1144

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Body Diameter:**

1.840 inches

#### Shaft Diameter:

0.2497 inches

### Shaft Length:

0.875 inches

### Mounting Bushing Length:

0.312 inches

#### Body Length:

2.062 inches

### **Overall Diameter:**

2.406 inches

Shaft Style:

Round

### Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

### Maximum Starting Torque:

15.00 centimeter-grams

### Maximum Running Torque:

15.00 centimeter-grams

### Maximum Stop Torque:

1000.00 inch-ounces

#### **Nonturn Device Location:**

At 6 oclock

### Nonturn Device Radius:

0.562 inches

### Shaft End Play:

0.005 inches

#### Shaft Runout:

0.002 inches

# Lateral Runout:

0.003 inches



Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.002 inches
Mechanical Backlash In Deg Angular Rotation:
10.0
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
100.0 ohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-2.0/+2.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:

3 tab, solder lug

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0