

View Online at <https://aerobasegroup.com/nsn/5905-01-149-1144>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

1.840 inches

**Shaft Diameter:**

0.2497 inches

**Shaft Length:**

0.875 inches

**Mounting Bushing Length:**

0.312 inches

**Body Length:**

2.062 inches

**Overall Diameter:**

2.406 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Maximum Starting Torque:**

15.00 centimeter-grams

**Maximum Running Torque:**

15.00 centimeter-grams

**Maximum Stop Torque:**

1000.00 inch-ounces

**Nonturn Device Location:**

At 6 oclock

**Nonturn Device Radius:**

0.562 inches

**Shaft End Play:**

0.005 inches

**Shaft Runout:**

0.002 inches

**Lateral Runout:**

0.003 inches

**Pilot Diameter Runout:**

0.002 inches

**Shaft Radial Play:**

0.002 inches

**Mechanical Backlash In Deg Angular Rotation:**

10.0

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Longitudinally positioned on the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

100.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Function Conformity Tolerance Per Section:**

-0.10/+0.10 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Power Dissipation Rating Per Section In Watts:**

5.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-2.0/+2.0 single section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

Single section linear

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0