

View Online at <https://aerobasegroup.com/nsn/5905-01-149-5386>

**Section Quantity:**

1

**Body Style:**

Cylindrical

**Reliability Indicator:**

Not established

**Terminal Length:**

0.141 inches

**Body Diameter:**

0.594 inches

**Body Length:**

0.196 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

260.0

**Maximum Starting Torque:**

6.00 inch-ounces

**Maximum Running Torque:**

6.00 inch-ounces

**Maximum Stop Torque:**

48.00 inch-ounces

**Center To Center Distance Between Terminals:**

0.344 inches

**Terminal Location:**

Lower adjacent side two rows

**Mounting Method:**

Terminal

**Center To Center Distance Between Terminal Rows:**

0.156 inches

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

2.500 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

260.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.172 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

**Resistance Tolerance Per Section In Percent:**

-30.0/+30.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0