## NSN 5905-01-149-5386

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-149-5386

Section Quantity:

**Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 0.141 inches **Body Diameter:** 0.594 inches **Body Length:** 0.196 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Center To Center Distance Between Terminals:** 0.344 inches **Terminal Location:** Lower adjacent side two rows **Mounting Method: Terminal Center To Center Distance Between Terminal Rows:** 0.156 inches **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 2.500 kilohms single section **Rotary Actuator Travel In Angular Deg:** 260.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.172 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section

0.25 free air single section

**Power Dissipation Rating Per Section In Watts:** 

## NSN 5905-01-149-5386

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-30.0/+30.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No