Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-149-5387

# Section Quantity:

1

Body Style:

Cylindrical

# **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.141 inches

#### **Body Diameter:**

0.594 inches

**Body Length:** 

0.196 inches

Actuator Type:

#### Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

260.0

## Maximum Starting Torque:

6.00 inch-ounces

#### Maximum Running Torque:

6.00 inch-ounces

# Maximum Stop Torque:

48.00 inch-ounces

# Center To Center Distance Between Terminals:

0.344 inches

# **Terminal Location:**

Lower adjacent side two rows

### Mounting Method:

Terminal

### Center To Center Distance Between Terminal Rows:

0.156 inches

### **Features Provided:**

Humidity proof

### **Electrical Resistance Per Section:**

5.000 kilohms single section

# Rotary Actuator Travel In Angular Deg:

260.0

# Center To Center Distance Between Center Terminal And Outside Terminal:

# 0.172 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.25 free air single section



# **Resistance Tolerance Per Section In Percent:**

-30.0/+30.0 single section

# Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0