## NSN 5905-01-150-4460

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-150-4460 **Section Quantity: Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Body Diameter:** 0.937 inches **Shaft Diameter:** Between 0.1242 inches and 0.1247 inches **Shaft Length:** 0.270 inches **Body Length:** 1.297 inches **Mounting Hole/stud Circle Diameter:** 0.562 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 305.0 **Maximum Starting Torque:** 0.50 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.002 inches **Pilot Diameter Runout:** 0.00100 inches **Shaft Radial Play:** 0.001 inches **Screw Thread Diameter:** 0.073 inches **Screw Thread Series Designator:** 

Unc Screw Thready Qty Per Inch (tpi): 64.0

## NSN 5905-01-150-4460

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
5.580 kilohms single section
Rotary Actuator Travel In Angular Deg:
345.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section absolute linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-10.0/+10.0 ohms single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
150.0 single section
Function Characteristic Per Section:
Single section table
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Special Features:
Gear assembly part no. 458288-001 assembled on back end of variable resistor
Test Data Document:
89305-485289-001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
4 wire lead
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5905-01-150-4460

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0