NSN 5905-01-150-4538

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-150-4538 **Section Quantity: Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Body Diameter:** 0.937 inches **Shaft Diameter:** 0.1247 inches **Shaft Length:** 0.305 inches **Body Length:** 0.561 inches **Mounting Hole/stud Circle Diameter:** 0.562 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 305.0 **Maximum Starting Torque:** 0.27 inch-ounces **Maximum Running Torque:** 0.27 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.002 inches

Pilot Diameter Runout: 0.00100 inches **Shaft Radial Play:** 0.001 inches **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.067 inches

NSN 5905-01-150-4538

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Screw Thread Series Designator:	
Unc	
Screw Thready Qty Per Inch (tpi):	
64.0	
Mounting Facility Quantity:	
2	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Threaded hole	
Features Provided:	
Humidity proof	
Cubic Measure:	
0.320 cubic inches	
Electrical Resistance Per Section:	
5.580 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
360.0	
Resistance Tempurature Characteristic Range Per Section In Percent:	
-5.0/+0.0 -65 degrees celsius single section and -5.0/+10.0 25 degrees celsius single section and -5.0/+10.0 125 degrees celsius single	
section	
Function Conformity Tolerance Per Section:	
-0.15/+0.15 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
-10.0/+10.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Terminal Type And Quantity:	
3 wire lead	
Shelf Life:	
N/a	
Unit Of Measure:	
	

No

Demilitarization:

NSN 5905-01-150-4538

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0