Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-150-6349

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Body Diameter:**

0.500 inches

#### Shaft Diameter:

0.125 inches

Shaft Length:

0.690 inches

Mounting Bushing Length:

#### 0.250 inches

**Body Length:** 

# 0.531 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Rear end

#### Mounting Method:

Standard bushing

#### **Features Provided:**

Shaft seal

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

#### Power Dissipation Rating Per Section In Watts:

0.2 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

### Standard Taper Curve Per Section:

F single section

### **Terminal Type And Quantity:**

3 tab, solder lug

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0