

View Online at <https://aerobasegroup.com/nsn/5905-01-150-8544>

Section Quantity:

2

Body Style:

Cylindrical hole/slot mounted

Reliability Indicator:

Not established

Body Diameter:

0.937 inches

Shaft Diameter:

Between 0.1242 inches and 0.1247 inches

Shaft Length:

0.330 inches

Body Length:

1.297 inches

Mounting Hole/stud Circle Diameter:

0.562 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

324.0

Maximum Starting Torque:

0.50 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00100 inches

Shaft Radial Play:

0.001 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.073 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

64.0

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

5.580 percent, rated amperes c and better finish

Rotary Actuator Travel In Angular Deg:

324.0

Function Conformity Tolerance Per Section:

-0.15/+0.15 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Power Dissipation Rating Per Section In Watts:

1.0 7th secondary finish

Function Conformity Per Section:

All sections absolute linearity

Fixed Tap Quantity Per Section:

1 1st section

Tap Location Tolerance Per Section:

-10.0/+10.0 ohms 1st section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Tap Location From Ccw Terminal Per Section In Ohms:

150.0 1st section

Function Characteristic Per Section:

All sections table

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Special Features:

Gear train assembly part n0. 485288-001 assembled on back end of variable resistor

Test Data Document:

89305-485289-002 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0