NSN 5905-01-151-4569

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-151-4569 **Section Quantity:** 1 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.094 inches **Overall Height:** 0.987 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.594 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 2.50 inch-ounces **Maximum Running Torque:** 2.50 inch-ounces **Maximum Stop Torque:** 64.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:**

Screw Thread Diameter: 0.250 inches

0.305 inches

NSN 5905-01-151-4569

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Terminal Location:	
Lower adjacent side two rows	
Mounting Method:	
Standard bushing	
Features Provided:	
Nonmetallic shaft	
Cubic Measure:	
0.232 cubic inches	
Electrical Resistance Per Section:	
25.000 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
300.0	
Resistance Tempurature Characteristic Range Per Section In Percent:	
+0.0/+7.0 -55 degrees celsius single section and +0.0/+3.5 -25 degrees celsius single section and -2.5/+2.5 85 degrees celsius single	
section and +0.0/+5.5 120 degrees celsius single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
100.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.5 free air single section	
Resistance Tolerance Per Section In Percent:	
-10.0/+10.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Special Features:	
Nonmetallic bushing	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	