NSN 5905-01-152-0076

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-152-0076 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** Between 0.969 inches and 1.031 inches **Mounting Bushing Length:** Between 0.300 inches and 0.330 inches **Body Length:** Between 0.980 inches and 1.020 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.005 inches **Pilot Diameter Runout:** 0.00200 inches **Shaft Radial Play:** 0.003 inches **Fragility Factor:** Moderately delicate

Screw Thread Diameter: 0.375 inches

NSN 5905-01-152-0076

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-300.0/+300.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Test Data Document:
82577-h950003 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
1 tab, solder lug and 2 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0