

View Online at <https://aerobasegroup.com/nsn/5905-01-152-1226>

Section Quantity:

2

Body Style:

Rectangular bushing mounted

Shaft Diameter:

0.250 inches

Shaft Length:

0.250 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.890 inches

Body Width:

0.625 inches

Body Height:

0.625 inches

Shaft Style:

Round, slotted

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0 and 28.0

Actuator Type:

Single shaft

Maximum Starting Torque:

3.20 inch-ounces

Nonturn Device Location:

At 3 oclock

Nonturn Device Radius:

0.327 inches

Switch Contact Arrangement:

Double pole, single throw, normally closed

Mounting Facility Quantity:

1

Terminal Location:

Right-left adjacent sides

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

5000.000 ohms single section

Function Conformity Tolerance Per Section:

-10.00/+10.00 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Switch Current Type And Rating In Amps:

2.000 ac and 2.000 dc

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0