

View Online at <https://aerobasegroup.com/nsn/5905-01-152-1226>

**Section Quantity:**

2

**Body Style:**

Rectangular bushing mounted

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.250 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.890 inches

**Body Width:**

0.625 inches

**Body Height:**

0.625 inches

**Shaft Style:**

Round, slotted

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

125.0 and 28.0

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

3.20 inch-ounces

**Nonturn Device Location:**

At 3 oclock

**Nonturn Device Radius:**

0.327 inches

**Switch Contact Arrangement:**

Double pole, single throw, normally closed

**Mounting Facility Quantity:**

1

**Terminal Location:**

Right-left adjacent sides

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

5000.000 ohms single section

**Function Conformity Tolerance Per Section:**

-10.00/+10.00 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-150.0/+150.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Switch Current Type And Rating In Amps:**

2.000 ac and 2.000 dc

**Terminal Type And Quantity:**

7 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0