NSN 5905-01-152-2568

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-152-2568

Electrical Resistance: 2,390 mejorhins Resistance Tolerance in Percent: -5,000/45,000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 100.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4100.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1,250 inches Body Diameter: Between 0,345 inches and 0,454 inches Body Length: Between 0,345 inches and 1,310 inches Power Dissipation Rating in Watts: 0,750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
2.900 megohms Resistance Tolerance in Percent: -5.000/45.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 100.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+100.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Length: Between 0.3930 inches and 1.310 inches Power Dissipation Rating in Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit of Measure:	-1000.0/+1000.0
Resistance Tolerance In Percent: -5.000/45-000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 100.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+100.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Between 0.345 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2556821 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Electrical Resistance:
-5.00045.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 100.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+100.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Diameter: Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	2.900 megohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 100.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+100.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Length: Between 0.395 inches and 0.454 inches Body Length: Between 0.390 inches and 1.310 inches Power Dissipation Rating in Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 100.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+100.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Diameter: Between 0.3930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558821 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 100.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+100.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Length: Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-100.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Botween 0.345 inches and 0.454 inches Body Diameter: Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+100.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Diameter: Between 0.345 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+100.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Diameter: Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	100.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Length: Between 0.390 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Length: Between 0.390 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-55.0/+100.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Length: Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Length: Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Encapsulated
Reliability Indicator: Not established Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Length: Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note stablished Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Length: Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Terminal Length: 1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Length: Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
1.250 inches Body Diameter: Between 0.345 inches and 0.454 inches Body Length: Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Between 0.345 inches and 0.454 inches Body Length: Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
Between 0.345 inches and 0.454 inches Body Length: Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.250 inches
Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
Between 0.930 inches and 1.310 inches Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.345 inches and 0.454 inches
Power Dissipation Rating In Watts: 0.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
O.750 free air Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.930 inches and 1.310 inches
Style Designator: Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.750 free air
Test Data Document: 10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	10001-2558621 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No No
A001a0	Fiig:
	A001a0