## NSN 5905-01-152-2580

**Section Quantity:** 

Cylindrical bushing mounted

Between 0.445 inches and 0.505 inches

Reliability Indicator:

Not established

Terminal Length:

**Body Style:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-152-2580

Body Diameter:
0.484 mils and 0.516 centimeters
Shaft Diameter:
0.125 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.250 inches
Body Length:
Between 0.437 inches and 0.469 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 250.0 and 270.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Maximum Stop Torque:
48.00 inch-ounces
Nonturn Device Location:
At 4'30 oclock and at 10'30 oclock
Nonturn Device Radius:
0.245 inches
Center To Center Distance Between Terminals:
Between 0.290 inches and 0.310 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.250 inches

## NSN 5905-01-152-2580

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Cubic Measure:
0.089 cubic inches
Electrical Resistance Per Section:
2.5 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 292.0 and 298.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.140 mils and 0.160 centimeters
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0/+150.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A002a0