## NSN 5905-01-152-4931

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-152-4931

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.200 inches
Shaft Diameter:
0.070 inches
Shaft Length:
0.045 inches
Body Length:
0.395 inches
Body Width:
0.240 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Maximum Starting Torque:
3.00 inch-ounces
Maximum Running Torque:
3.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Rugged
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
100.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## NSN 5905-01-152-4931

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 7th secondary quality **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**