NSN 5905-01-152-6868

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-152-6868

Section Quantity
Section Quantity:
Body Style:
Cylindrical Reliability Indicator:
Not established
Body Diameter:
0.785 inches
Body Length: 0.422 inches
Actuator Type: Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
240.0
Maximum Starting Torque: 8.00 inch-ounces
Maximum Running Torque:
8.00 inch-ounces
Fragility Factor:
Moderately delicate Terminal Location:
Rear end
Mounting Method: Tab and terminal
Features Provided:
Grounded contact arm
Electrical Resistance Per Section:
1.5 kilohms single section
Rotary Actuator Travel In Angular Deg:
240.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops Ambient Tempurature In Dec Coloius Per Section At Full Peter Bower.
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-01-152-6868

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



T	er	minal	Тур	Э	And	Quantity:	
_							

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0