## NSN 5905-01-153-2466

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-153-2466 **Section Quantity:** 1 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.625 inches **Terminal Length:** 0.220 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.825 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.750 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.305 inches

**Shaft End Play:** 

0.014 inches

## NSN 5905-01-153-2466

Precision Wire Wound Variable Resistor - Page 2 of 3



**Shaft Runout:** 0.006 inches **Shaft Radial Play:** 0.005 inches **Center To Center Distance Between Terminals:** 0.400 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side two rows **Mounting Method:** Standard bushing **Center To Center Distance Between Terminal Rows:** 0.200 inches **Cubic Measure:** 0.293 cubic inches **Electrical Resistance Per Section:** 1.5 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 3600.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.300 inches **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.8 7th secondary quality **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section

7 oclock all primaries

**Function Characteristic Per Section:** 

## NSN 5905-01-153-2466

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0