NSN 5905-01-154-6137

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-154-6137

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -1.000/+1.000 Electrical Resistance: 2.430 megohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.090 inches Body Length: 0.250 free air Unpackaged Unit Weight: 0.500 grams Style Designator:
Electrical Resistance: 2.430 megohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 ograms
2.430 megohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 orgams
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Pailure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams
0.250 free air Unpackaged Unit Weight: 0.500 grams
Unpackaged Unit Weight: 0.500 grams
0.500 grams
•
Style Designator:
Asial tampinal and and
Axial terminal each end
Test Data Document:
81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39017/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-01-154-6137

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0