NSN 5905-01-154-6750

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-154-6750

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|--|
| -30.0/+30.0 |
| Electrical Resistance: |
| 232.000 ohms |
| Resistance Tolerance In Percent: |
| -1.000/+1.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 275.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+275.0 |
| Inclosure Method: |
| Encased |
| Terminal Type: |
| Tab, solder lug |
| Reactance Characteristic: |
| Inductive |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 1.000 |
| Terminal Length: |
| 0.312 inches |
| Body Length: |
| 0.750 inches |
| Body Width: |
| 0.438 inches |
| Body Height: |
| 0.406 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 0.562 inches |
| Power Dissipation Rating In Watts: |
| 10.000 heat sink |
| Terminal Width: |
| 0.140 inches |
| Mounting Hole Size: |
| 0.094 inches |
| Style Designator: |
| Axial terminal (s) |
| Test Data Document: |

81349-mil-r-39009/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5905-01-154-6750

Wire Wound Fixed Resistor - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0