## NSN 5905-01-155-4908

Thermal Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-155-4908

Reliability Indicator:
Not established
Terminal Surface Treatment:
Solder
Terminal Length:
1.500 inches
Body Length:
0.406 inches
Body Outside Diameter:
0.140 inches
Terminal Diameter:
0.025 inches
Ambient Tempurature At Full Rated Power:
100.0 degrees celsius
Maximum Operating Temp:
150.0 degrees celsius
Thermal Time Constant In Seconds:
60.0
Power Dissipation Constant In Milliwatts Per Deg Celsius:
4.5
Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius:
Zero Fower Tempurature Coemicient of Resistance in Fercent Fer Deg Cersius.
4.20
4.20
4.20 Tempurature Points For Resistance Readings At Zero Power:
<ul> <li>4.20</li> <li>Tempurature Points For Resistance Readings At Zero Power:</li> <li>75.0 degrees celsius 7th resistance-temperature point</li> </ul>
4.20 Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp:
4.20 Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point
4.20 Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent:
Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -19.0/+19.0 1st resistance-temperature point
4.20 Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -19.0/+19.0 1st resistance-temperature point End Application:
4.20 Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -19.0/+19.0 1st resistance-temperature point End Application: Remote readout hygrothermometer transmitter (rrht)
4.20 Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -19.0/+19.0 1st resistance-temperature point End Application: Remote readout hygrothermometer transmitter (rrht) Inclosure Type:
Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -19.0/+19.0 1st resistance-temperature point End Application: Remote readout hygrothermometer transmitter (rrht) Inclosure Type: Encapsulated
Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -19.0/+19.0 1st resistance-temperature point End Application: Remote readout hygrothermometer transmitter (rrht) Inclosure Type: Encapsulated Cubic Measure:
Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -19.0/+19.0 1st resistance-temperature point End Application: Remote readout hygrothermometer transmitter (rrht) Inclosure Type: Encapsulated Cubic Measure: 0.006 cubic inches
Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -19.0/+19.0 1st resistance-temperature point End Application: Remote readout hygrothermometer transmitter (rrht) Inclosure Type: Encapsulated Cubic Measure: 0.006 cubic inches Zero Power Resistance:
Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -19.0/+19.0 1st resistance-temperature point End Application: Remote readout hygrothermometer transmitter (rrht) Inclosure Type: Encapsulated Cubic Measure: 0.006 cubic inches Zero Power Resistance: 680.000 ohms
Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -19.0/+19.0 1st resistance-temperature point End Application: Remote readout hygrothermometer transmitter (rrht) Inclosure Type: Encapsulated Cubic Measure: 0.006 cubic inches Zero Power Resistance: 680.000 ohms Zero Power Resistance Tolerance In Percent At Reference Temp:
Tempurature Points For Resistance Readings At Zero Power: 75.0 degrees celsius 7th resistance-temperature point Zero Power Resistance At Specificationified Temp: 952.0 ohms 7th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -19.0/+19.0 1st resistance-temperature point End Application: Remote readout hygrothermometer transmitter (rrht) Inclosure Type: Encapsulated Cubic Measure: 0.006 cubic inches Zero Power Resistance: 680.000 ohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0

0.9 grams

## NSN 5905-01-155-4908

Thermal Resistor - Page 2 of 2



Style Designator:
Rod
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A086a0