## NSN 5905-01-155-9722

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-155-9722

-5.0/4-5.0 Electrical Resistance: 1.000 ohms Resistance Tolerance In Percent: -5.000/4-5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 355.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4-350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.406 inches Body Diameter: 0.406 inches Body Diameter: 0.406 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 64859-84-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
1.000 ohms Resistance Tolerance In Percent: -5.000/-5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.406 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No	5.0/+5.0
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 35.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.406 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: B4959-4ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.406 inches Body Diameter: 0.406 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	1.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0  Inclosure Method: Encapsulated Terminal Type: Wire lead  Reliability Indicator: Not established Terminal Length: 1.500 inches  Body Diameter: 0.406 inches  Body Length: 1.000 inches  Power Dissipation Rating In Watts: 5.000 free air  Style Designator: Axial terminal each end Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.406 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.406 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 50.000 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.406 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.406 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.406 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	350.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.406 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Fempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.500 inches  Body Diameter:  0.406 inches  Body Length:  1.000 inches  Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	55.0/+350.0
Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 1.500 inches  Body Diameter: 0.406 inches  Body Length: 1.000 inches  Power Dissipation Rating In Watts: 5.000 free air  Style Designator: Axial terminal each end  Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a	nclosure Method:
Wire lead  Reliability Indicator:  Not established  Terminal Length: 1.500 inches  Body Diameter: 0.406 inches  Body Length: 1.000 inches  Power Dissipation Rating In Watts: 5.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	Encapsulated
Reliability Indicator:  Not established  Terminal Length:  1.500 inches  Body Diameter:  0.406 inches  Body Length:  1.000 inches  Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	Ferminal Type:
Not established  Terminal Length:  1.500 inches  Body Diameter:  0.406 inches  Body Length:  1.000 inches  Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	Nire lead
Terminal Length:  1.500 inches  Body Diameter:  0.406 inches  Body Length:  1.000 inches  Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	Reliability Indicator:
1.500 inches  Body Diameter: 0.406 inches  Body Length: 1.000 inches  Power Dissipation Rating In Watts: 5.000 free air  Style Designator: Axial terminal each end  Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a	Not established
Body Diameter:  0.406 inches  Body Length:  1.000 inches  Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	Гerminal Length:
0.406 inches  Body Length: 1.000 inches  Power Dissipation Rating In Watts: 5.000 free air  Style Designator: Axial terminal each end  Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a	I.500 inches
Body Length:  1.000 inches  Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	Body Diameter:
1.000 inches  Power Dissipation Rating In Watts: 5.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	0.406 inches
Power Dissipation Rating In Watts:  5.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	Body Length:
5.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	I.000 inches
Style Designator:  Axial terminal each end  Test Data Document:  64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	5.000 free air
Test Data Document: 64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a	Style Designator:
64959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a	Геst Data Document:
Shelf Life: N/a	34959-ks-14603 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
	Shelf Life:
Unit Of Measure:	N/a
	Jnit Of Measure:
<del></del>	-
Demilitarization:	Demilitarization:
No	No
Fiig:	Filg:
A001a0	A001a0