NSN 5905-01-157-2758

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-157-2758

One them Over them
Section Quantity:
Body Style:
Cylindrical
Reliability Indicator:
Not established
Terminal Length:
0.141 inches
Overall Height:
1.156 inches
Overall Width:
0.594 inches
Body Diameter:
0.594 inches
Body Length:
0.156 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
40.00 inch-ounces
Center To Center Distance Between Terminals:
0.344 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.156 inches
Features Provided:
Humidity proof
Electrical Resistance Per Section:
550.000 ohms single section
Rotary Actuator Travel In Angular Deg:
260.0
Center To Center Distance Between Center Terminal And Outside Terminal:

0.172 inches

NSN 5905-01-157-2758

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:** No