## NSN 5905-01-158-2338

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-158-2338
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-300.0/+300.0
Electrical Resistance:
100.000 kilohms
Resistance Tolerance In Percent:
-5.000/+5.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
14
Terminal Type:
Pin
Reliability Indicator:
Not established
Terminal Length:
Between 0.250 inches and 0.350 inches
Body Length:
0.305 inches
Body Width:
0.375 inches
Body Height:
0.075 inches
Schematic Diagram Designator:
Ladder network
Power Dissipation Rating In Watts:
0.325 total network
Terminal Width:
0.017 inches
Identical Value Resistor Quantity:
13 each resistor
Unpackaged Unit Weight:
1.300 grams
Style Designator:
Flat pack
Test Data Document:

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5905-01-158-2338

Film Fixed Resistor Network - Page 2 of 2



_				_	
٧n	<b>ACIT</b>	100	tion	า Data	٠.
Ju	CUII	ıva	uui	ı valc	1.

81349-mil-r-83401/3 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0