

View Online at <https://aerobasegroup.com/nsn/5905-01-159-5518>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.578 inches

First Flat Length:

0.250 inches

Flat Height:

Between 0.092 inches and 0.096 inches

Body Diameter:

0.500 inches

Shaft Diameter:

Between 0.124 inches and 0.126 inches

Shaft Length:

0.750 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.594 inches

Overall Diameter:

0.500 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Sleeve

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0 and 28.0

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

248.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Maximum Stop Torque:

64.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.240 inches and 0.250 inches

Mechanical Backlash In Deg Angular Rotation:

3.0

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear-bottom

Mounting Method:

Standard bushing

Features Provided:

Panel seal and switch

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

295.0

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+7.0 -55 degrees celsius single section and +0.0/+3.5 -25 degrees celsius single section and +0.0/+2.0 0 degrees celsius single section and -2.5/+2.5 85 degrees celsius single section and +0.0/+5.5 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Switch Current Type And Rating In Amps:

0.500 ac and 1.500 dc

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0