

View Online at <https://aerobasegroup.com/nsn/5905-01-159-7572>

Section Quantity:

1

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Thread Length:

0.750 inches

Shaft Diameter:

0.250 inches

Shaft Length:

3.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

3.750 inches

Body Width:

1.250 inches

Body Height:

1.250 inches

Shaft Style:

Round, threaded

Actuator Type:

Single shaft

Longitudinal Actuator Travel:

2.625 inches

Longitudinal Actuator Effective Electrical Stroke Length:

2.500 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Cubic Measure:

5.859 cubic inches

Electrical Resistance Per Section:

1.0 kilohms single section

Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Power Dissipation Rating Per Section In Watts:

8.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location Tolerance Per Section:

-10.0/+10.0 ohms single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Tap Location From Ccw Terminal Per Section In Ohms:

500.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0