NSN 5905-01-160-7105

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-160-7105

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -50.0 to 50.0 Electrical Resistance: 16.670 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length:
Electrical Resistance: 16.670 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
16.670 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
-1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
-15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Terminal Type: Wire lead Reliability Indicator: Not established
Wire lead Reliability Indicator: Not established
Reliability Indicator: Not established
Not established
Terminal Length:
1.500 inches
Body Diameter:
0.230 inches
Body Length:
0.480 inches
Power Dissipation Rating In Watts:
3.000 free air
Precious Material And Location:
Terminal surfaces gold
Style Designator:
Axial terminal each end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0