NSN 5905-01-160-8646

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-160-8646

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.187 inches
Body Length:
Between 0.130 inches and 0.170 inches
Body Width:
0.300 inches
Body Height:
Between 0.360 inches and 0.390 inches
Shaft Bearing Type:
Bearing
Actuator Type:
Flush drive with slot-hole
Center To Center Distance Between Terminals:
Between 0.190 inches and 0.210 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Rear end
Mounting Method:
Terminal
Features Provided:
Humidity proof
Cubic Measure:
0.017 cubic inches
Electrical Resistance Per Section:
1.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.090 inches and 0.110 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section

NSN 5905-01-160-8646

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No