

View Online at <https://aerobasegroup.com/nsn/5905-01-161-0869>

Section Quantity:

1

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Terminal Length:

4.32 millimeters

Shaft Diameter:

3.0 millimeters

Shaft Length:

16.0 millimeters

Mounting Bushing Length:

7.0 millimeters

Body Length:

10.0 millimeters

Body Width:

10.0 millimeters

Body Height:

10.0 millimeters

Shaft Style:

Round

Switch Type:

Rotary

Switch Voltage Rating In Volts:

17.0

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

220.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Maximum Stop Torque:

32.00 inch-ounces

Switch Operating Position:

End of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Center To Center Distance Between Terminals:

5.08 millimeters

Screw Thread Diameter:

7.0 millimeters

Screw Thread Series Designator:

Iso m

Screw Thready Qty Per Inch (tpi):

34.0

Terminal Location:

Lower adjacent side single row

Mounting Method:

Standard bushing

Features Provided:

Switch and nonmetallic shaft

Cubic Measure:

1000.000 cubic centimeters

Electrical Resistance Per Section:

470.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Center To Center Distance Between Center Terminal And Outside Terminal:

2.54 millimeters

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

Power Dissipation Rating Per Section In Watts:

0.1 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Switch Current Type And Rating In Amps:

0.400 dc

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0