
Film Fixed Resistor Network - Page 1 of 2



# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

#### **Electrical Resistance:**

2.200 kilohms

## **Resistance Tolerance In Percent:**

-5.000/+5.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Quantity:**

16

#### **Terminal Type:**

Tab, solder lug

# Reliability Indicator:

Not established

#### **Terminal Length:**

0.135 inches

#### Body Length:

0.830 inches

#### **Body Width:**

0.270 inches

#### **Body Height:**

0.135 inches

#### Schematic Diagram Designator:

Ladder network

#### **Power Dissipation Rating In Watts:**

1.500 total network

#### **Terminal Width:**

0.022 inches

#### Identical Value Resistor Quantity:

15 each resistor

## **Unpackaged Unit Weight:**

1.500 grams

#### Style Designator:

Dual inline

#### **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).



Film Fixed Resistor Network - Page 2 of 2



**Specification Data:** 

81349-mil-r-83401/2 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0