

View Online at <https://aerobasegroup.com/nsn/5905-01-161-6176>

**Section Quantity:**

2

**Body Style:**

Rectangular w/bushing

**Reliability Indicator:**

Not established

**Shaft Diameter:**

Between 0.248 inches and 0.250 inches

**Shaft Length:**

1.219 inches

**Mounting Bushing Length:**

1.500 inches

**Body Length:**

1.359 inches

**Body Width:**

1.156 inches

**Body Height:**

Between 1.688 inches and 1.812 inches

**Undercut Diameter:**

Between 0.124 inches and 0.126 inches

**Shaft Style:**

Round, stepped

**Actuator Type:**

Dual concentric

**Nonturn Device Location:**

At 9 o'clock

**Nonturn Device Radius:**

Between 0.526 inches and 0.536 inches

**Undercut Length:**

0.219 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

2.500 kilohms all sections

**Power Dissipation Rating Per Section In Watts:**

0.5 free air all sections

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Special Features:**

Both shafts ground flat

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0