

View Online at https://aerobasegroup.com/nsn/5905-01-162-5625

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### Body Diameter:

1.844 centimeters

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.750 inches

#### Mounting Bushing Length:

0.313 inches

#### Body Length:

2.094 inches

# Shaft Style:

Round, slotted

# Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

3600.0

# Maximum Starting Torque:

2.00 inch-ounces

#### Maximum Running Torque:

1.00 inch-ounces

#### Maximum Stop Torque:

160.00 inch-ounces

#### Nonturn Device Location:

At 12 oclock

#### Nonturn Device Radius:

0.562 inches

# Shaft End Play:

0.005 inches

#### Shaft Runout:

0.002 inches

#### Lateral Runout:

0.002 inches

# **Pilot Diameter Runout:**

0.001 inches

# Shaft Radial Play:

0.002 inches

0.5

Unef

32.0



# Mechanical Backlash In Deg Angular Rotation: Screw Thread Diameter: 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.0 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 5.0 7th secondary quality **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** 7 oclock all primaries Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Test Data Document:** 81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 turret **Specification Data:** 81349-mil-r-12934/32 government specification Shelf Life:

Unit Of Measure:

N/a



Demilitarization:

No

Fiig:

A002a0