Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-162-6273

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.670 inches

#### Shaft Diameter:

0.251 inches

#### Shaft Length:

1.181 inches

#### Mounting Bushing Length:

0.046 inches

#### Body Length:

0.417 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Tab

#### **Electrical Resistance Per Section:**

150.0 kilohms single section

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

80.0 single section

# Power Dissipation Rating Per Section In Watts:

0.25 free air single section

# **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

# Terminal Type And Quantity:

3 tab, solder lug

# Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

# NSN 5905-01-162-6273

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

