NSN 5905-01-163-3120

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-163-3120 **Section Quantity: Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Terminal Length:** 0.500 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.625 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 1.50 inch-ounces **Maximum Stop Torque:** 64.00 inch-ounces **Nonturn Device Location:**

At 9 oclock **Nonturn Device Radius:** 0.305 inches **Center To Center Distance Between Terminals:** 0.200 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef

NSN 5905-01-163-3120

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing
Center To Center Distance Between Terminal Rows:
0.200 inches
Cubic Measure:
0.244 cubic inches
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Resistance Tempurature Characteristic Range Per Section In Percent:
5.5/+5.5 -55 degrees celsius single section and -3.0/+3.0 -25 degrees celsius single section and -3.0/+3.0 85 degrees celsius single section
and -5.0/+5.0 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0