Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-163-5726

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Terminal Length:**

0.250 inches

## First Flat Length:

0.375 inches

## Flat Height:

0.172 inches

## Body Diameter:

0.891 inches

## Shaft Diameter:

0.250 inches

# Shaft Length:

onart Longtin.

0.438 inches

## Mounting Bushing Length:

0.250 inches

## Body Length:

0.688 inches

## Shaft Style:

Round, flatted

## Actuator Type:

Single shaft

## **Center To Center Distance Between Terminals:**

0.313 inches

## Screw Thread Diameter:

0.250 inches

# Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

200.0 kilohms single section

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.313 inches

# NSN 5905-01-163-5726 Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

60.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.1 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

10.0 single section

## **Special Features:**

Shaft end chamfered 0.034 in

## **Terminal Type And Quantity:**

3 pin

## Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A002a0