NSN 5905-01-164-8951

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-164-8951

| Section Quantity: |
|--|
| 1 |
| Body Style: |
| Rectangular bushing mounted |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.500 inches |
| Shaft Diameter: |
| 0.125 inches |
| Shaft Length: |
| 0.875 inches |
| Mounting Bushing Length: |
| 0.375 inches |
| Body Length: |
| 0.625 inches |
| Body Width: |
| 0.625 inches |
| Body Height: |
| 0.625 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 260.0 |
| Maximum Starting Torque: |
| 2.50 inch-ounces |
| Maximum Running Torque: |
| 2.50 inch-ounces |
| Maximum Stop Torque: |
| 64.00 inch-ounces |
| Nonturn Device Location: |
| At 9 oclock |
| Nonturn Device Radius: |
| 0.305 inches |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Screw Thread Diameter: |
| 0.250 inches |
| Screw Thread Series Designator: |

Unef

NSN 5905-01-164-8951

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Screw Thready Qty Per Inch (tpi): |
|---|
| 32.0 |
| Terminal Location: |
| Lower adjacent side two rows |
| Mounting Method: |
| Standard bushing |
| Center To Center Distance Between Terminal Rows: |
| 0.200 inches |
| Cubic Measure: |
| 0.244 cubic inches |
| Electrical Resistance Per Section: |
| 5.000 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 300.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.200 inches |
| Resistance Tempurature Characteristic Range Per Section In Percent: |
| +0.0/+5.5 -55 degrees celsius single section and +0.0/+3.0 -25 degrees celsius single section and -2.0/+2.0 85 degrees celsius single |
| section and +0.0/+4.5 120 degrees celsius single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 120.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.75 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |