Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-165-0088

## Section Quantity:

1

Body Style:

Rectangular

## Reliability Indicator:

Not established

#### **Terminal Length:**

0.200 inches

#### Shaft Diameter:

0.070 inches

Shaft Length:

0.035 inches

Body Length:

#### 0.250 inches

Body Width:

## 0.175 inches

**Body Height:** 

0.250 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Maximum Starting Torque:

3.00 inch-ounces

#### Maximum Running Torque:

3.00 inch-ounces

#### **Center To Center Distance Between Terminals:**

0.200 inches

#### **Terminal Location:**

Lower adjacent side two rows

#### **Mounting Method:**

Terminal

#### Center To Center Distance Between Terminal Rows:

0.100 inches

#### **Features Provided:**

Grounded contact arm

#### **Electrical Resistance Per Section:**

5.000 kilohms single section

### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# NSN 5905-01-165-0088 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-10.0/+10.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Terminal Type And Quantity:** 

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0