# NSN 5905-01-165-0668

Hybrid Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-165-0668

# Section Quantity:

1

Body Style:

Cylindrical friction mounted

# **Reliability Indicator:**

Not established

## Thread Length:

0.250 inches

#### Body Diameter:

0.750 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.500 inches

#### Body Length:

14.000 inches

#### Shaft Style:

Round, threaded

#### Actuator Type:

Single shaft

#### Longitudinal Actuator Travel:

9.842 inches

#### Longitudinal Actuator Effective Electrical Stroke Length:

9.842 inches

## Fragility Factor:

Moderately rugged

#### **Terminal Location:**

Rear end

#### Mounting Method:

Clamp

#### **Features Provided:**

Humidity proof

#### **Electrical Resistance Per Section:**

10.0 percent, rated amperes c and better flooring

#### Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-125.0/+125.0 single section

# Power Dissipation Rating Per Section In Watts:

0.02 7th secondary quality

# NSN 5905-01-165-0668

Hybrid Variable Resistor - Page 2 of 2



Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Function Characteristic Per Section:

7 oclock all primaries

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

20.0 single section

#### **Special Features:**

Eyelet extension on shaft

#### Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

#### Fiig:

A002a0