## NSN 5905-01-165-1694

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-165-1694

Electrical Resistance: 3.830 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 30.0/+110.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.140 inches Body Diameter: 0.140 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.040 free air Style Designator: Axial terminal each end Test Data Document: 00063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: — Demilitarization: No Filig:	
Electrical Resistance: 3.830 kilohms Resistance Tolerance In Percent: 1.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 30.0/+110.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 1.140 inches Body Length: 3.380 inches Power Dissipation Rating In Watts: 1.040 free air Style Designator: Xival terminal seach end Test Data Document: 100063-enc-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, stac; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: ————————————————————————————————————	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.0001+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 130.0/+110.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Resilability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.140 inches Body Diameter: 0.440 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.040 free air Style Designator: Avial terminal each end Test Data Document: 80063-sm~-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, steel; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Via Unit of Measure: ————————————————————————————————————	+45.0/+55.0
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -30.0/s-110.0 Inclosure Method: -50.0cspsulated Terminal Type:	Electrical Resistance:
Annown to Degree of Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 30.0/+110.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.140 inches Body Diameter: 0.140 inches Body Diameter: 0.140 inches Body Diameter: 0.140 inches Body Length: 0.380 inches Power Dissipation Rating in Watts: 0.040 free air Style Designator: Avial terminal each end Test Data Document: Style Designator: Avial terminal each end Test Data Document: Unit Of Measure: ————————————————————————————————————	3.830 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 30.0/+110.0  Inclosure Method: Encapsulated  Terminal Type: Wire laad  Reliability Indicator: Not established  Terminal Length: 1,500 inches  Body Diameter: 0,140 inches  Body Length: 0,380 inches  Power Dissipation Rating In Watts: 0,040 free air Style Designator: Axial terminal each end  Test Data Document: style Designator: Axial terminal each end  Test Data Document: style Designator: Axial terminal each end  Test Data Document: style Designator: Axial terminal each end  Test Data Document: style Designator: Axial terminal each end  Test Data Document: style Designator: Axial terminal each end  Test Data Document: Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  30.0/+110.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.500 inches  Body Diameter:  1.140 inches  Body Diameter:  1.340 inches  Prower Dissipation Rating In Watts:  1.040 free air  Style Designator:  Avaid terminal each end  Test Data Document:  10005-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Via  Unit Of Measure:  — Demilitarization:  No  Filig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 30.0/4110.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Not established  Terminal Length: 1.500 inches  Body Diameter: 0.140 inches  Body Diameter: 0.140 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.040 free air  Style Designator: Akala terminal each end  Test Data Document: 30063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, atc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Via  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 30.04+110.0 inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.140 inches Body Diameter: 0.140 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.040 free air Style Designator: Avial terminal each end Test Data Document: 80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, stc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  30.0/+110.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.500 inches  Body Diameter:  0.140 inches  Body Length:  0.380 inches  Power Dissipation Rating In Watts:  0.040 free air  Style Designator:  Axial terminal each end  Test Data Document:  80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, ster; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wire Life	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Note established Ferminal Length: 1.500 inches Body Diameter: 0.140 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.040 free air Style Designator: Axial terminal each end Fest Data Document: 80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, sheft Life: N/a Unit Of Measure:	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.500 inches Body Diameter: 0.140 inches Body Diameter: 0.380 inches Power Dissipation Rating In Watts: 0.390 inches Power Dissipation Rating In Watts: 0.396 besignator: Axial terminal each end Fest Data Document: 83063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.140 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.040 free air Style Designator: Avial terminal each end Test Data Document: 80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Filig:	-30.0/+110.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.500 inches  Body Diameter:  0.140 inches  Body Length:  0.380 inches  Power Dissipation Rating In Watts:  0.040 free air  Style Designator:  Axial terminal each end  Test Data Document:  80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  No  Unit Of Measure:  Demilitarization:  No  Filg:	Inclosure Method:
Wire lead  Reliability Indicator: Not established  Terminal Length: 1.500 inches  Body Diameter: 0.140 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.040 free air  Style Designator: Axial terminal each end  Test Data Document: 30063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: No  Demilitarization: No  Filig:	Encapsulated
Reliability Indicator: Not established  Terminal Length: 1.500 inches  Body Diameter: 0.140 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.040 free air  Style Designator: Axial terminal each end  Test Data Document: 80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:	Terminal Type:
Note established  Terminal Length:  1.500 inches  Body Diameter:  0.140 inches  Body Length:  0.380 inches  Power Dissipation Rating In Watts:  0.040 free air  Style Designator:  Axial terminal each end  Test Data Document:  80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Wire lead
Terminal Length:  1.500 inches  Body Diameter:  0.140 inches  Body Length:  0.380 inches  Power Dissipation Rating In Watts:  0.040 free air  Style Designator:  Axial terminal each end  Test Data Document:  80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:  No  Filig:	Reliability Indicator:
1.500 inches Body Diameter: 0.140 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.040 free air Style Designator: Axial terminal each end Test Data Document: 80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Not established
Body Length: 0.140 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.040 free air Style Designator: Axial terminal each end Test Data Document: 80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Length:
20.140 inches  Body Length: 20.380 inches  Power Dissipation Rating In Watts: 20.040 free air  Style Designator:  Axial terminal each end  Test Data Document:  80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	1.500 inches
Body Length:  0.380 inches  Power Dissipation Rating In Watts:  0.040 free air  Style Designator:  Axial terminal each end  Test Data Document:  80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Body Diameter:
D.380 inches  Power Dissipation Rating In Watts:  0.040 free air  Style Designator:  Axial terminal each end  Test Data Document:  30063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	0.140 inches
Power Dissipation Rating In Watts:  0.040 free air  Style Designator:  Axial terminal each end  Test Data Document:  0.0063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Body Length:
O.040 free air  Style Designator:  Axial terminal each end  Test Data Document:  B0063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	0.380 inches
Style Designator: Axial terminal each end  Test Data Document: B0063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	0.040 free air
Test Data Document:  80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Style Designator:
80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Axial terminal each end
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	80063-sm-c-883867 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
N/a Unit Of Measure: Demilitarization: No Fiig:	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	<del></del>
Fiig:	Demilitarization:
	No
<del>1</del> 001a0	Fiig:
	A001a0